



CY-2020-FA "N"

- **Built In Safety Features**
- **Readily Transportable**
- **Economical Operation**
- **Clean Burning**

Designed for Petroleum, Mining, and Lumber Industries

Capacity

0.6 m³, 64 kg per hour.
type No. 1, 2, & 3 waste.

Power Requirements

115 volts 60 cycle single phase.

Stack

Stainless Steel - 14 gauge
- 33 cm diameter
- 3 m high
- c/w stainless steel
spark arrester
- a hinged base plate for
moving

Casing

12 gauge steel.
Lining: high heat duty castable refractory
over high temperature insulation.

Hearth

Refractory hearth over 6.35 mm steel
base

Doors

6.35 cm steel plate c/w heavy duty blade
latch.
Charging: - 46 cm x 61 cm clear opening
- Refractory lined over steel plate
Ash: - 46 cm x 30 cm clear opening
- Refractory lined over steel plate

Air Supply

Forced air fan c/w duct to primary air jets
and to secondary over-fire air jets.

Timers

Cycle timer interconnected to air supply
fan and gun type burner enclosed in
burner housing.

Burners

500,000 B.T.U. gun type primary burner.
Gun burner enclosed in protective plate
steel housing.
300,000 B.T.U. in secondary chamber

Fuel Supply: Oil Fired Unit Only

1350 litre fuel storage tank c/w filter and
flexible hose type connection.

Transporter

Incinerator and fuel storage mounted on
skid type frame 365 cm long x 152 cm
wide.
Height: 2.64 M tall, with stack folded.
Constructed of 15 cm I Beam c/w bumper
posts.

Weight

2268 kg.

Options

- * L.P.G. Fired burner
- * Diesel fired burner
- * 2.3 m Electric power cord
- * Stack winch
- * 1.4 m³ model 2050.
- * Cold climate assembly.

MANUFACTURED BY:

DISTRIBUTED BY:



Environmental Services Inc.

20204 – 110 Avenue, Edmonton, AB Canada T5S 1X8

Phone: (780) 447-5052 Fax: (780) 447-4912

E-MAIL info@westlandenvironmental.com